

Manual

01 Installation:

You can mount your D-Odor either on wall or on the ceiling.

The unit should be installed indoors away from Window/doors and exhaust fan for best results. The unit should have enough space, both in front and rear, to be to suck and throw out air.

02 Mounting:



- Make holes on the wall/ceiling as per the holes on the mounting plate.
- Bolt the mounting plate on the wall with 4 screws. Match the holes on the side of the mounting plate with the holes on the rear of the unit. Bolt the unit with 4 screws on the mounting plate, from the side.
- Ensure that screws are properly tightened up.
- Plug the adaptor in a regular 220V AC supply.

03 Maintenance:

a) Pre Filter

- There is a pre-filter on the rear end of the unit. it is to keep the insect and thick particle away.
- It can be pulled out for cleaning. It is recommended to clean this filter atleast once a month, depending on how dirty/choked it is. Insert the pre-filter back after cleaning it under a running tap.



b) Reactor Cassette

D-odor cassette, which is on the centre of the unit can also be pulled out. It has our patented technology quoting. You may clean this cassette without touching/rubbing the mesh cell inside under normal water running tap, delicately. Depending on the usage, it is recommended to get it replaced atleast once in 6 months for best results.



Warranty

Your D-odor comes with 1 year comprehensive warranty, for electrical failure. Physical damages are excluded for warranty.